Hand protection

FC115

THERMAL WELDING WORKS

Thermal leather glove, ideal for welding work in heavy industry



Specific benefits

Performance

· The high-performance HEATnocut fiber provides resistance to contact heat (100°C for 15 seconds)

Applications

- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Maintenance**
- **Automotive**
- **Temporary work**

Certifications and norms

CE CATEGORY II

EN 388
2 1 3 2 X

EN 12477
TYPE B

EN 407
4 1 2 X 4 X

Protects against risks

Heat

Wearing

Hand protection

FC115

THERMAL WELDING WORKS

Thermal leather glove, ideal for welding work in heavy industry

Standards - Details



EN388:2016+A1:2018
2 [0-4] ABRASION RESISTANCE
1 [0-5] CUT RESISTANCE
3 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
X [A-F] CUT RESISTANCE ISO 13997



EN 407
THERMAL RISKS (X = NOT TESTED)
4 [0-4] BURNING BEHAVIOUR
1 [0-4] CONTACT HEAT RESISTANCE
2 [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
4 [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Welding glove
Mechanical glove kind	Cut and sewn
Thickness (mm)	0,9
Arm level protection	Forearm cuff (< 400mm)
Cuff caracteristic	Leather cuff
Color	Grey
Size	10
Type of packaging	Bulk bag of 12

Packaging

Sale unit: Bulk bag of 12
60 pairs /box