Fall protection

AN203200ZD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips



Specific benefits

Hygiene

· Harnesses and textiles can be washed with neutral soap

Performance

· Strap with improved abrasion resistance and certified for use on sharp edges

· Certification above the maximum rated load of 100 kg: product certified at 140 kg

Applications

- **Public works**
- **Finishing works / Craftsmanship**
- **Automotive**
- **Storage**

Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Protects against risks

Fall

Fall protection

AN203200ZD

ENERGY ABSORBING LANYARDS

Energy absorbing lanyard made of high impact webbing, for short trips

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Polyester
Length (m)	2
Gate opening (mm)	55
Opening (inch)	2.1616
Lock	Automatic system
With connector	yes
Fall factor	F2
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 18mm
Ending	2 sewn thimble loops
Connector (structure side)	1 automatic lock hook, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1
Fall arrest work situations	Vertical movement on a permanent structure, Movement on lifeline, Short vertical movement or movement on inclined surface (less than 3 m), Short horizontal movement (less than 3 m)
Lenght (ft)	6.5616