Fall protection

PROTECTOR TETRA AN15006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres



Certifications and norms

CE CATEGORY III

EN360
RFU 11.062
150 KG

Protects against risks

Fall

Specific benefits

Performance

· Certification above the maximum rated load of 100 kg: product certified at 150 kg

Easy to use

· Automatic carabiners for secure and time-saving locking
· Carrying handle for easy transport
· NFC system guarantees traceability

Durability

· Impact-resistant ABS housing

Visibility

· Visual fall indicator for instant verification that the product is working properly

Applications

- **Building**
- **Maintenance**
- **Chemical industry**
- **Petrochemical**
- **Storage**

Fall protection

PROTECTOR TETRA AN15006T

RETRACTABLE FALL ARRESTERS

Self-retractable cable fall arrester for distances of up to 6 metres

Standards - Details

Technical details

Type of equipment	Cable reel
Composition of the main support	ABS, Galvanized steel
Max. length (m)	6
ARA lenght (m)	6
ARA lenght (inch)	236.2206
Cable diameter (mm)	4
Included elements	Included energy absorber
Color	Orange
Connector (user side)	Small hook, steel, opening 21 mm
Benefits element	Fall indicator
Lifespan from manufacturing (years)	20
Weight (kg)	5,6
Maximum load for one person (kg)	150
Fall arrest work situations	Vertical movement on a permanent structure, Long vertical movement or movement on inclined surface
Locking system	Inertia locking system
Use of self retracting	Vertical