Hand protection

EOS FLEX CUT D VV922

LONG-LASTING CUT WORK

Impact-resistant glove with level D cut protection for the whole hand, ideal for multi-purpose work in aqueous or oily environments



Certifications and norms

CE CATEGORY II

EN 388
3 X 4 2 D P

EN 407
X 2 X X X X

Protects against risks

Heat | Shock | Cutting | Wearing

Specific benefits

Durability

· High-quality coating extends the life of the glove and provides excellent protection for the hand

Easy to use

· Perfect fit so that users do not feel any discomfort in the wrist area with prolonged use

Hygiene

· Reduces perspiration thanks to its excellent breathability

Performance

· Flexible reinforcements for added protection against impact and pinching
· SOFTnocut fiber provides excellent cut resistance

Applications

- **Agriculture**
- **Public works**
- **Building**
- **Finishing works / Craftsmanship**
- **Maintenance**
- **Automotive**

Hand protection

EOS FLEX CUT D VV922

LONG-LASTING CUT WORK

Impact-resistant glove with level D cut protection for the whole hand, ideal for multi-purpose work in aqueous or oily environments

Standards - Details

EN388:2016+A1:2018
3 [0-4] ABRASION RESISTANCE
X [0-5] CUT RESISTANCE
4 [0-4] TEAR RESISTANCE
2 [0-4] PIERCE RESISTANCE
D [A-F] CUT RESISTANCE ISO 13997
P [P] IMPACT RESISTANCE (OPTIONAL)

EN 407
X [0-4] BURNING BEHAVIOUR
2 [0-4] CONTACT HEAT RESISTANCE
X [0-4] CONVECTIVE HEAT
X [0-4] RADIANT HEAT RESISTANCE
X [0-4] SMALL DROP MOLTEN METAL
X [0-4] LARGE QUANTITY MOLTEN METAL

Technical details

Glove kind	Special glove
Glove family	Impact-resistant glove
Tight glove kind	Unsupported
Mechanical glove kind	Knitted
Special gloves kind	Impact
Weft yarn	SOFTnocut (Mixed HDPE /Spandex / polyamide)
Coating level	Fully coated
Coating material	Thermoplastic
Coating finition	Smooth
Number of layer	Single layer
Gauge	15
Color	Black
Size	9
Type of packaging	Header card

Packaging

Sale unit: Header card
60 pairs /box