Fall protection

AN213150ZDD

ENERGY ABSORBING LANYARDS

Double energy-absorbing lanyard in high-strength webbing for short movements.



Specific benefits

Hygiene

· Harnesses and textiles can be washed with neutral soap

Performance

· Strap with improved abrasion resistance and certified for use on sharp edges

· Certification above the maximum rated load of 100 kg: product certified at 140 kg

Applications

- **Public works**
- **Automotive**
- **Power Energy**
- **Storage**

Certifications and norms

CE CATEGORY III

EN355
HORIZONTAL CERTIFICATION - 140 KG
RFU 11.062
140 KG

Fall protection

AN213150ZDD

ENERGY ABSORBING LANYARDS

Double energy-absorbing lanyard in high-strength webbing for short movements.

Standards - Details

Technical details

Type of equipment	Flat webbing lanyard with energy absorber
Composition of the main support	Steel, Polyester
Length (m)	1,5
Lock	Automatic system
With connector	yes
Color	Orange
Connector (user side)	Automatic lock hook, steel, opening 19mm
Ending	2 sewn thimble loops
Connector (structure side)	2 automatic lock hooks, steel, opening 55 mm
Lifespan from manufacturing (years)	10
Weight (kg)	1,4
Maximum load for one person (kg)	140
Lenght (ft)	4.9213