Head protection

VISOR FLASH 2

SAFETY VISORS

Arc protection visor, 14cal/cm^2 ASTM, curved chin protection to minimise discomfort to the user's movements.



Certifications and norms

CE

EN170
UV 2C - 1.7

EN166
1 FT 8

GS-ET-29
8-1-1

ASTM F 2178-12
14 CAL/CM² - 1+2

ANSI Z87.1 - IMPACT
Z87+ U6 L1.7

Specific benefits

Comfort

· Curved chin protector, no discomfort in the user's movements

Performance

· Impact and splash resistant molded lens

Durability

· Anti-scratch coating Increasing lifespan

Compatibility

· Fits slotted safety caps

Benefits elements

· Color perception
· Large field of view

Applications

- **Building**
- **Finishing works / Craftsmanship**
- **Light industry**
- **Maintenance**
- **Automotive**



Head protection

VISOR FLASH 2

SAFETY VISORS

Arc protection visor, 14cal/cm^2 ASTM, curved chin protection to minimise discomfort to the user's movements.

Standards - Details

Technical details

Use	Inside/outside
Type of eye protection	Face shield
Lens matérial	Polycarbonate
Lens treatment	Anti-fogging (classic), Anti-scratch (classic), UV400
Lens color	Green
Optical class	1
Lens protection class	1.7
Mechanical strength (lens)	F, T
Weight (g)	230
Type of packaging	Sold individually